

Appendix C

Cocol grammar for the Clang compiler/interpreter

This appendix gives the Cocol specification and frame file for constructing a compiler for the Clang language as developed by the end of Chapter 18, along with the source for the tree-building code generator.

clang.atg | cgen.h | cgen.cpp | clang.frm

```
----- clang.atg -----
$CX
COMPILER Clang
/* CLANG level 4 grammar - function, procedures, parameters, concurrency
   Display model.
   Builds an AST for code generation.
   P.D. Terry, Rhodes University, 1996 */

#include "misc.h"
#include "set.h"
#include "table.h"
#include "report.h"
#include "cgen.h"

typedef Set<7> classset;

bool debug;
int blocklevel;
TABLE_idclasses blockclass;

extern TABLE *Table;
extern CGEN *CGen;

/*-----*/
IGNORE CASE
IGNORE CHR(9) .. CHR(13)
COMMENTS FROM "(*" TO "*")"

CHARACTERS
  cr      = CHR(13) .
  lf      = CHR(10) .
  letter  = "ABCDEFHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz" .
  digit   = "0123456789" .
  instrng = ANY - '"' - cr - lf .

TOKENS
  identifier = letter { letter | digit } .
  number     = digit { digit } '""' { instrng | "'''" } '""' .
  string     = '""' (instrng | "'''" ) { instrng | "'''" } '""' .

PRODUCTIONS
  Clang          = ". TABLE_entries entry; TABLE_index index; ."
  "PROGRAM"      =
  Ident<entry.name> = ". debug = (strcmp(entry.name, \"DEBUG\") == 0);"
                     ". entry.idclass = TABLE_progs;"
                     ". Table->enter(entry, index);"
                     ". Table->openscope(); ."
  WEAK ";"       =
  Block<entry.level+1, TABLE_progs, 0> =
  " ." .

  Block<int blklevel, TABLE_idclasses blkclass, int initialframesize> =
  " ." .
                     ". int framesize = initialframesize;"
                     ". CGEN_labels entrypoint;"
                     ". CGen->jump(entrypoint, CGen->undefined);"
                     ". if (blklevel > CGEN_levmax) SemError(213); ."
  SYNC
  { ( ConstDeclarations
    | VarDeclarations<framesize>
```

```

    | ProcDeclaration
) SYNC } (. /* blockclass, blocklevel global for efficiency */
blockclass = blkclass; blocklevel = blklevel;
CGen->backpatch(entrypoint);
/* reserve space for variables */
CGen->openstackframe(framesize
                      - initialframesize); .)

CompoundStatement (. switch (blockclass)
{ case TABLE_progs :
  CGen->leaveprogram(); break;
  case TABLE_procs :
  CGen->leaveprocedure(blocklevel); break;
  case TABLE_funcs :
  CGen->functioncheck(); break;
}
if (debug) /* demonstration purposes */
  Table->printtable(stdout);
Table->closescope(); .).

ConstDeclarations
= "CONST" OneConst { OneConst } .

OneConst (. TABLE_entries entry; TABLE_index index; .)
Ident<entry.name> (. entry.idclass = TABLE_consts; .)
WEAK "="
Number<entry.c.value> (. Table->enter(entry, index) .)
";" .

VarDeclarations<int &framesize>
= "VAR" OneVar<framesize> { WEAK "," OneVar<framesize> } ";" .

OneVar<int &framesize> (. TABLE_entries entry; TABLE_index index;
entry.idclass = TABLE_vars; entry.v.ref = false;
entry.v.size = 1; entry.v.scalar = true;
entry.v.offset = framesize + 1; .)
Ident<entry.name>
[ UpperBound<entry.v.size> (. entry.v.scalar = false; .)
] (. Table->enter(entry, index);
   framesize += entry.v.size; .).

UpperBound<int &size>
= "[" Number<size> "]" (. size++; .).

ProcDeclaration
= (" PROCEDURE"
  | "FUNCTION"
) Ident<entry.name> (. TABLE_entries entry; TABLE_index index; .)
(. entry.idclass = TABLE_procs; .)
(. entry.idclass = TABLE_funcs; .)
(. entry.p.params = 0; entry.p.paramsize = 0;
entry.p.firstparam = NULL;
CGen->storelabel(entry.p.entrypoint);
Table->enter(entry, index);
Table->openscope() .)
[
FormalParameters<entry> (. Table->update(entry, index) .)
] WEAK ";"
Block<entry.level+1, entry.idclass, entry.p.paramsize + CGEN_headersize>
";" .

FormalParameters<TABLE_entries &proc>
= (" OneFormal<proc, proc.p.firstparam>
  { WEAK "," OneFormal<proc, p> } ")" .

OneFormal<TABLE_entries &proc, TABLE_index &index>
= (. TABLE_entries formal;
formal.idclass = TABLE_vars; formal.v.ref = false;
formal.v.size = 1; formal.v.scalar = true;
formal.v.offset = proc.p.paramsize
                  + CGEN_headersize + 1 .)
Ident<formal.name>
[ "[" "]"
] (. formal.v.size = 2; formal.v.scalar = false;
formal.v.ref = true; .)
(. Table->enter(formal, index);
proc.p.paramsize += formal.v.size;
proc.p.params++; .).

CompoundStatement
= "BEGIN" Statement { WEAK ";" Statement } "END" .

Statement
= SYNC [ CompoundStatement | AssignmentOrCall | ReturnStatement

```

```

] . | IfStatement      | WhileStatement
    | CobeginStatement | SemaphoreStatement
    | ReadStatement   | WriteStatement
    | "STACKDUMP"     | (. CGen->dump(); .)

AssignmentOrCall
= (. TABLE_entries entry;
   AST des, exp; .)
Designator<des, classset(TABLE_vars, TABLE_procs), entry, true>
( /* assignment */ (. if (entry.idclass != TABLE_vars) SemError(210); .)
  := Expression<exp, true>
  SYNC (. CGen->assign(des, exp); .)
  | /* procedure call */ (. if (entry.idclass < TABLE_procs)
    { SemError(210); return; }
    CGen->markstack(des, entry.level,
                      entry.p.entrypoint); .)
ActualParameters<des, entry>
( . CGen->call(des); .)
) .

Designator<AST &D, classset allowed, TABLE_entries &entry, bool entire>
= (. TABLE_alfa name;
   AST index, size;
   bool found;
   D = CGen->emptyast(); .)
Ident<name>
( . Table->search(name, entry, found);
  if (!found) SemError(202);
  if (!allowed.memb(entry.idclass)) SemError(206);
  if (entry.idclass != TABLE_vars) return;
  CGen->stackaddress(D, entry.level, entry.v.offset,
                       entry.v.ref); .)
( "[ "
  Expression<index, true>
  (. if (!entry.v.scalar) SemError(204); .)
  (. if (!entry.v.scalar)
     /* determine size for bounds check */
     { if (entry.v.ref)
       CGen->stackaddress(size, entry.level,
                           entry.v.offset + 1, false);
     else
       CGen->stackconstant(size, entry.v.size);
     CGen->subscript(D, entry.v.ref, entry.level,
                      entry.v.offset, size, index);
     } .)
  "]"
  (. if (!entry.v.scalar)
   { if (entire) SemError(205);
     if (entry.v.ref)
       CGen->stackaddress(size, entry.level,
                           entry.v.offset + 1, false);
     else
       CGen->stackconstant(size, entry.v.size);
     CGen->stackreference(D, entry.v.ref, entry.level,
                           entry.v.offset, size);
   } .)
) .

ActualParameters<AST &p, TABLE_entries proc>
= [ "(" (. int actual = 0; .)
  OneActual<p, (*Table).isrefparam(proc, actual)>
  { WEAK ","
    OneActual<p, (*Table).isrefparam(proc, actual)> } ")"
  (. if (actual != proc.p.params) SemError(209); .)
]

OneActual<AST &p, bool byref>
= (. AST par; .)
  Expression<par, !byref> (. if (byref && !CGen->isrefast(par)) SemError(214);
                            CGen->linkparameter(p, par); .).

ReturnStatement
= (. AST dest, exp; .)
"RETURN"
( (. if (blockclass != TABLE_funcs) SemError(219);
   CGen->stackaddress(dest, blocklevel, 1, false); .)
  Expression<exp, true>
  (. CGen->assign(dest, exp);
   CGen->leavefunction(blocklevel); .)
  | /* empty */
    (. switch (blockclass)
      { case TABLE_procs :
        CGen->leaveprocedure(blocklevel); break;
        case TABLE_progs :
        CGen->leaveprogram(); break;
      }
    )
)

```

```

        case TABLE_funcs : SemError(220); break;
    } .)

IfStatement
=
(. CGEN_labels testlabel;
AST C; .)
"IF" Condition<C> "THEN" (. CGen->jumpontfalse(C, testlabel, CGen->undefined) .)
Statement (. CGen->backpatch(testlabel); .).

WhileStatement
=
"WHILE"
Condition<C> "DO"
Statement (. CGEN_labels startloop, testlabel, dummylabel;
AST C; .)
(. CGen->storelabel(startloop) .)
(. CGen->jumpontfalse(C, testlabel, CGen->undefined) .)
(. CGen->jump(dummylabel, startloop);
CGen->backpatch(testlabel) .).

Condition<AST &C>
=
(. AST E;
CGEN_operators op; .)
Expression<C, true>
(" RelOp<op>
  Expression<E, true> (. CGen->comparison(op, C, E); .)
  | /* Missing op */ (. SynError(91) .)
) .

CobeginStatement
=
"COBEGIN"
(. int processes = 0;
CGEN_labels start; .)
ProcessCall (. if (blockclass != TABLE_progs) SemError(215);
CGen->cobegin(start); .)
{ WEAK ";" ProcessCall (. processes++; .)
}
"COEND" (. processes++; .)
(. CGen->coend(start, processes); .).

ProcessCall
=
(. TABLE_entries entry;
AST P; .)
Designator<P, classset(TABLE_procs), entry, true>
(. if (entry.idclass < TABLE_procs) return;
CGen->markstack(P, entry.level,
entry.p.entrypoint); .)
ActualParameters<P, entry>
(. CGen->forkprocess(P); .).

SemaphoreStatement
=
(" WAIT"
| "SIGNAL"
)
(" Variable<sem> (. if (wait) CGen->waitop(sem);
else CGen->signalop(sem); .)
") .

ReadStatement
=
"READ" "(" Variable<V>
{ WEAK "," Variable<V> (. AST V; .)
} ")" (. CGen->readvalue(V); .)
(. CGen->readvalue(V); .)

Variable<AST &V>
=
Designator<V, classset(TABLE_vars), entry, true> (. TABLE_entries entry; .)

WriteStatement
=
"WRITE" [ "(" WriteElement { WEAK "," WriteElement } ")" ]
(. CGen->newline(); .).

WriteElement
=
(. AST exp;
char str[600];
CGEN_labels startstring; .)
String<str> (. CGen->stackstring(str, startstring);
CGen->writestring(startstring); .)
| Expression<exp, true> (. CGen->writevalue(exp) .).

Expression<AST &E, bool entire>
=
(. AST T;
CGEN_operators op;
E = CGen->emptyast(); .)

```

```

(   "+" Term<E, true>      (. CGen->negateinteger(E); .)
|   "-" Term<E, true>      (. CGen->negateinteger(E); .)
|   Term<E, entire>
}
{ AddOp<op> Term<T, true>(. CGen->binaryintegerop(op, E, T); .)
} .

Term<AST &T, bool entire>
=
Factor<T, entire>          (. AST F;
                           CGEN_operators op; .)
{
  ( MulOp<op>
    | /* missing op */
    ) Factor<F, true>      (. SynError(92); op = CGEN_opmul; .)
}
} .

Factor<AST &F, bool entire>
=
Designator<F, classset(TABLE_consts, TABLE_vars, TABLE_funcs), entry, entire>
(. switch (entry.idclass)
  { case TABLE_consts :
     CGen->stackconstant(F, entry.c.value);
     return;
   case TABLE_procs :
   case TABLE_funcs :
     CGen->markstack(F, entry.level,
                       entry.p.entrypoint); break;
   case TABLE_vars :
   case TABLE_progs :
     return;
  } .)
ActualParameters<F, entry>
Number<value>              (. CGen->stackconstant(F, value) .)
(" Expression<F, true> " ) .

AddOp<CGEN_operators &op>
=
  "+"                      (. op = CGEN_opadd; .)
  | "-"                     (. op = CGEN_opsub; .) .

MulOp<CGEN_operators &op>
=
  "*"                      (. op = CGEN_opmul; .)
  | "/"                     (. op = CGEN_opdvd; .) .

RelOp<CGEN_operators &op>
=
  "="                      (. op = CGEN_opeql; .)
  | "<>"                 (. op = CGEN_opneq; .)
  | "<"                    (. op = CGEN_oplss; .)
  | "<="                   (. op = CGEN_opleq; .)
  | ">"                    (. op = CGEN_opgtr; .)
  | ">="                   (. op = CGEN_opgeq; .) .

Ident<char *name>
= identifier                (. LexName(name, TABLE_alfalength); .) .

String<char *str>
= string
(. char local[100];
LexString(local, sizeof(local) - 1);
int i = 0;
while (local[i]) /* strip quotes */
{ local[i] = local[i+1]; i++; }
local[i-2] = '\0';
i = 0;
while (local[i]) /* find internal quotes */
{ if (local[i] == '\'')
  { int j = i;
    while (local[j])
    { local[j] = local[j+1]; j++; }
  }
  i++;
}
strcpy(str, local); .) .

Number <int &num>
= number
(. char str[100];
int i = 0, l, digit, overflow = 0;
num = 0;
LexString(str, sizeof(str) - 1);
l = strlen(str);
while (i <= l && isdigit(str[i])) {
  digit = str[i] - '0'; i++;
  if (num <= (maxint - digit) / 10)

```

```

        num = 10 * num + digit;
        else overflow = 1;
    }
if (overflow) SemError(200); . .

```

END Clang.

----- cgen.h -----

```

// Code Generation for Clang level 4 compiler/interpreter
// AST version for stack machine (OOP)
// Includes procedures, functions, parameters, arrays, concurrency.
// Display machine.
// P.D. Terry, Rhodes University, 1996

#ifndef CGEN_H
#define CGEN_H

#include "misc.h"
#include "stkmc.h"
#include "report.h"

#define CGEN_headersize  STKMC_headersize
#define CGEN_levmax      STKMC_levmax

enum CGEN_operators {
    CGEN_opadd, CGEN_opsub, CGEN_opmul, CGEN_opdvd, CGEN_opeql, CGEN_opneq,
    CGEN_oplss, CGEN_opgeq, CGEN_opgtr, CGEN_opleq
};

struct NODE;
typedef NODE *AST;
typedef short CGEN_labels;

class CGEN {
public:
    CGEN_labels undefined; // for forward references

    CGEN(REPORT *R);
    // Initializes code generator

    AST emptyast(void);
    // Returns an empty (undefined) AST

    bool isrefast(AST a);
    // Returns true if a corresponds to a reference AST

    void negateinteger(AST &i);
    // Generates code to negate integer i

    void binaryintegerop(CGEN_operators op, AST &l, AST &r);
    // Generates code to perform infix operation op on l, r

    void comparison(CGEN_operators op, AST &l, AST &r);
    // Generates code to perform comparison operation op on l, r

    void readvalue(AST i);
    // Generates code to read value for i

    void writevalue(AST i);
    // Generates code to output value i

    void newline(void);
    // Generates code to output line mark

    void writestring(CGEN_labels location);
    // Generates code to output string stored at known location

    void stackstring(char *str, CGEN_labels &location);
    // Stores str in literal pool in memory and return its location

    void stackconstant(AST &c, int number);
    // Creates constant AST for constant c from number

    void stackaddress(AST &v, int level, int offset, bool byref);
    // Creates address AST for variable v with known level, offset

    void dereference(AST &a);
    // Generates code to replace address a by the value stored there

    void stackreference(AST &base, bool byref,
                        int level, int offset, AST &size);
}

```

```

// Creates an actual parameter node for a reference parameter corresponding
// to an array with given base and size

void subscript(AST &base,
              int level, int offset, AST &size, AST &index);
// Prepares to apply an index to an array with given base, with checks
// that the limit on the bounds is not exceeded

void assign(AST dest, AST expr);
// Generates code to store value of expr on dest

void openstackframe(int size);
// Generates code to reserve space for size variables

void leaveprogram(void);
// Generates code needed to leave a program (halt)

void leaveprocedure(int blocklevel);
// Generates code needed to leave a regular procedure at a given blocklevel

void leavefunction(int blocklevel);
// Generates code needed to leave a function at given blockLevel

void functioncheck(void);
// Generates code to ensure that a function has returned a value

void storelabel(CGEN_labels &location);
// Stores address of next instruction in location for use in backpatching

void jump(CGEN_labels &here, CGEN_labels destination);
// Generates unconditional branch from here to destination

void jumponfalse(AST condition, CGEN_labels &here, CGEN_labels destination);
// Generates branch from here to destination, dependent on condition

void backpatch(CGEN_labels location);
// Stores the current location counter as the address field of the branch
// instruction currently held in an incomplete form at location

void markstack(AST &p, int level, int entrypoint);
// Generates code to reserve mark stack storage before calling procedure p
// with known level and entrypoint

void linkparameter(AST &p, AST &par);
// Adds par to the actual parameter list for call to procedure p

void call(AST &p);
// Generates code to enter procedure p

void cobegin(CGEN_labels &location);
// Generates code to initiate concurrent processing

void coend(CGEN_labels location, int number);
// Generates code to terminate concurrent processing

void forkprocess(AST &p);
// Generates code to initiate process p

void signalop(AST s);
// Generates code for semaphore signalling operation on s

void waitop(AST s);
// Generates code for semaphore wait operation on s

void dump(void);
// Generates code to dump the current state of the evaluation stack

void getsize(int &codeLength, int &initSP);
// Returns length of generated code and initial stack pointer

int gettop(void);
// Returns codetop

void emit(int word);
// Emits single word

private:
    REPORT *Report;
    bool generatingCode;
    STKMC_address codetop, stktop;
    void binaryop(CGEN_operators op, AST &left, AST &right);
};

}

```

```

#endif /*CGEN_H*/

----- cgen.cpp -----
// Code Generation for Clang Level 4 compiler/interpreter
// AST version for stack machine (OOP)
// Includes procedures, functions, parameters, arrays, concurrency.
// Display machine.
// P.D. Terry, Rhodes University, 1996

#include "misc.h"
#include "cgen.h"
#include "report.h"

extern STKMC *Machine;
extern CGEN *CGen;
extern REPORT *Report;

// ++++++ AST node classes ++++++
struct NODE {
    int value;          // value derived from this node
    bool defined;       // true if value is defined (for constant nodes)
    bool refnode;       // true if node corresponds to a reference
    NODE() { defined = false; refnode = false; }
    virtual void emit1(void) = 0;
    virtual void emit2(void) = 0;
    virtual void link(AST next) = 0;
};

struct BINOPNODE : public NODE {
    CGEN_operators op;
    AST left, right;
    BINOPNODE(CGEN_operators O, AST L, AST R) { op = O; left = L; right = R; }
    virtual void emit1(void); // load value onto stack
    virtual void emit2(void) { ; }
    virtual void link(AST next) { ; }
};

void BINOPNODE::emit1(void)
// load value onto stack resulting from binary operation
{ bool folded = false;
if (left && right)
{ // Some optimizations (others are left as an exercise).
  // These need improvement so as to perform range checking
  switch (op)
  { case CGEN_opadd:
      if (right->defined && right->value == 0) // x + 0 = x
          { left->emit1(); folded = true; }
      else if (left->defined && left->value == 0) // 0 + x = x
          { right->emit1(); folded = true; }
      break;

    case CGEN_opsub:
      if (right->defined && right->value == 0) // x - 0 = x
          { left->emit1(); folded = true; }
      else if (left->defined && left->value == 0) // 0 - x = -x
          { right->emit1(); CGen->emit(int(STKMC_neg)); folded = true; }
      break;

    case CGEN_opmul:
      if (right->defined && right->value == 1) // x * 1 = x
          { left->emit1(); folded = true; }
      else if (left->defined && left->value == 1) // 1 * x = x
          { right->emit1(); folded = true; }
      else if (right->defined && right->value == 0) // x * 0 = 0
          { right->emit1(); folded = true; }
      else if (left->defined && left->value == 0) // 0 * x = 0
          { left->emit1(); folded = true; }
      break;

    case CGEN_opdvd:
      if (right->defined && right->value == 1) // x / 1 = x
          { left->emit1(); folded = true; }
      else if (right->defined && right->value == 0) // x / 0 = error
          { Report->error(224); folded = true; }
      break;
    // no folding attempted here for relational operations
  }
}
if (!folded)
{ if (left) left->emit1(); if (right) right->emit1();

```

```

    CGen->emit(int(STKMC_add) + int(op)); // careful - ordering used
}
if (left) delete left; if (right) delete right;
}

struct MONOPNODE : public NODE {
    CGEN_operators op; // for expansion - only negation used here
    AST operand;
    MONOPNODE(CGEN_operators O, AST E) { op = O; operand = E; }
    virtual void emit1(void); // load value onto stack
    virtual void emit2(void) { ; }
    virtual void link(AST next) { ; }
};

void MONOPNODE::emit1(void)
// load value onto stack resulting from unary operation
{ if (operand) { operand->emit1(); delete operand; }
    CGen->emit(int(STKMC_neg));
}

struct VARNODE : public NODE {
    bool ref; // direct or indirectly accessed
    int level; // static level of declaration
    int offset; // offset of variable assigned by compiler
    VARNODE() { ; } // default
    VARNODE(bool byref, int L, int O)
    { ref = byref; level = L; offset = O; }
    virtual void emit1(void); // load variable value onto stack
    virtual void emit2(void); // load variable address onto stack
    virtual void link(AST next) { ; }
};

void VARNODE::emit1(void)
// load variable value onto stack
{ emit2(); CGen->emit(int(STKMC_val)); }

void VARNODE::emit2(void)
// load variable address onto stack
{ CGen->emit(int(STKMC_adr)); CGen->emit(level); CGen->emit(-offset);
    if (ref) CGen->emit(int(STKMC_val));
}

struct INDEXNODE : public VARNODE {
    AST size; // for range checking
    AST index; // subscripting expression
    INDEXNODE(bool byref, int L, int O, AST S, AST I)
    { ref = byref; level = L; offset = O; size = S; index = I; }
    virtual void emit2(void); // load array element address and check
    virtual void link(AST next) { ; }
};

void INDEXNODE::emit2(void)
// load array element address and check in range
{ CGen->emit(int(STKMC_adr)); CGen->emit(level); CGen->emit(-offset);
    if (ref) CGen->emit(int(STKMC_val));
    if (index) { index->emit1(); delete index; }
    if (size) { size->emit1(); delete size; }
    CGen->emit(int(STKMC_ind));
}

// void INDEXNODE::emit1(void) is inherited from VARNODE

struct REFNODE : public VARNODE {
    AST size;
    REFNODE(bool byref, int L, int O, AST S)
    { ref = byref; level = L; offset = O; size = S; refnode = 1; }
    virtual void emit1(void); // load array argument address and size
    virtual void emit2(void) { ; }
    virtual void link(AST next) { ; }
};

void REFNODE::emit1(void)
// load array argument address and size
{ CGen->emit(int(STKMC_adr)); CGen->emit(level); CGen->emit(-offset);
    if (ref) CGen->emit(int(STKMC_val));
    if (size) { size->emit1(); delete size; }
}

struct CONSTNODE : public NODE {
    CONSTNODE(int V) { value = V; defined = true; }
    virtual void emit1(void); // load constant value onto stack
    virtual void emit2(void) { ; }
    virtual void link(AST next) { ; }
};

```

```

};

void CONSTNODE::emit1(void)
// load constant value onto stack
{ CGen->emit(int(STKMC_lit)); CGen->emit(value); }

struct PARAMNODE : public NODE {
    AST par, next;
    PARAMNODE(AST P) { par = P; next = NULL; }
    virtual void emit1(void); // load actual parameter onto stack
    virtual void emit2(void) {};
    virtual void link(AST param) { next = param; }
};

void PARAMNODE::emit1(void)
// load actual parameter onto stack
{ if (par) { par->emit1(); delete par; }
  if (next) { next->emit1(); delete next; } // follow link to next parameter
}

struct PROCNODE : public NODE {
    int level, entrypoint; // static level and first instruction
    AST firstparam, lastparam; // pointers to argument list
    PROCNODE(int L, int ent)
        { level = L; entrypoint = ent; firstparam = NULL; lastparam = NULL; }
    virtual void emit1(void); // generate procedure/function call
    virtual void emit2(void); // generate process call
    virtual void link(AST next); // link next actual parameter
};

void PROCNODE::emit1(void)
// generate procedure/function call
{ CGen->emit(int(STKMC_mst));
  if (firstparam) { firstparam->emit1(); delete firstparam; }
  CGen->emit(int(STKMC_cal));
  CGen->emit(level);
  CGen->emit(entrypoint);
}

void PROCNODE::emit2(void)
// generate process call
{ CGen->emit(int(STKMC_mst));
  if (firstparam) { firstparam->emit1(); delete firstparam; }
  CGen->emit(int(STKMC_frk));
  CGen->emit(entrypoint);
}

void PROCNODE::link(AST param)
// link next actual parameter
{ if (!firstparam) firstparam = param; else lastparam->link(param);
  lastparam = param;
}

// ++++++ code generator constructor ++++++
CGEN::CGEN(REPORT *R)
{ undefined = 0; // for forward references (exported)
  Report = R;
  generatingcode = true;
  codetop = 0;
  stktop = STKMC_memsize - 1;
}

void CGEN::emit(int word)
// Code generator for single word
{ if (!generatingcode) return;
  if (codetop >= stktop) { Report->error(212); generatingcode = false; }
  else { Machine->mem[codetop] = word; codetop++; }
}

bool CGEN::isrefast(AST a)
{ return a && a->refnode; }

// ++++++ routines that build the tree ++++++
AST CGEN::emptyast(void)
{ return NULL; }

void CGEN::negateinteger(AST &i)
{ if (i && i->defined) { i->value = -i->value; return; } // simple folding
  i = new MONOPNODE(CGEN_opsub, i);
}

```

```

void CGEN::binaryop(CGEN_operators op, AST &left, AST &right)
{ if (left && right && left->defined && right->defined)
  { // simple constant folding - better range checking needed
    switch (op)
    { case CGEN_opadd: left->value += right->value; break;
      case CGEN_opsub: left->value -= right->value; break;
      case CGEN_opmul: left->value *= right->value; break;
      case CGEN_opdvd:
        if (right->value == 0) Report->error(224);
        else left->value /= right->value;
        break;
      case CGEN_oplss: left->value = (left->value < right->value); break;
      case CGEN_opgtr: left->value = (left->value > right->value); break;
      case CGEN_opleq: left->value = (left->value <= right->value); break;
      case CGEN_opgeq: left->value = (left->value >= right->value); break;
      case CGEN_opeql: left->value = (left->value == right->value); break;
      case CGEN_opneq: left->value = (left->value != right->value); break;
    }
    delete right;
    return;
  }
  left = new BINOPNODE(op, left, right);
}

void CGEN::binaryintegerop(CGEN_operators op, AST &l, AST &r)
{ binaryop(op, l, r); }

void CGEN::comparison(CGEN_operators op, AST &l, AST &r)
{ binaryop(op, l, r); }

void CGEN::stackconstant(AST &c, int number)
{ c = new CONSTNODE(number); }

void CGEN::stackaddress(AST &v, int level, int offset, bool byref)
{ v = new VARNODE(byref, level, offset); }

void CGEN::linkparameter(AST &p, AST &par)
{ AST param = new PARAMNODE(par); p->link(param); }

void CGEN::stackreference(AST &base, bool byref, int level, int offset,
                         AST &size)
{ if (base) delete base; base = new REFNODE(byref, level, offset, size); }

void CGEN::subscript(AST &base, bool byref, int level, int offset,
                     AST &size, AST &index)
// Note the folding of constant indexing of arrays, and compile time
// range checking
{ if (!index || !index->defined || !size || !size->defined)
  { if (base) delete base;
    base = new INDEXNODE(byref, level, offset, size, index);
    return;
  }
  if (unsigned(index->value) >= size->value) // range check immediately
    Report->error(223);
  else
  { if (base) delete base;
    base = new VARNODE(byref, level, offset + index->value);
  }
  delete index; delete size;
}

void CGEN::markstack(AST &p, int level, int entrypoint)
{ p = new PROCNODE(level, entrypoint); }

// ++++++ code generation requiring tree walk ++++++
void CGEN::jumponfalse(AST condition, CGEN_labels &here,
                      CGEN_labels destination)
{ if (condition) { condition->emit1(); delete condition; }
  here = codetop; emit(int(STKMC_bze)); emit(destination);
}

void CGEN::assign(AST dest, AST expr)
{ if (dest) { dest->emit2(); delete dest; }
  if (expr) { expr->emit1(); delete expr; emit(int(STKMC_sto)); }
}

void CGEN::readvalue(AST i)
{ if (i) { i->emit2(); delete i; } emit(int(STKMC_inn)); }

void CGEN::writevalue(AST i)
{ if (i) { i->emit1(); delete i; } emit(int(STKMC_prn)); }

```

```

void CGEN::call(AST &p)
{ if (p) { p->emit1(); delete p; } }

void CGEN::signalop(AST s)
{ if (s) { s->emit2(); delete s; } emit(int(STKMC_sig)); }

void CGEN::waitop(AST s)
{ if (s) { s->emit2(); delete s; } emit(int(STKMC_wgt)); }

void CGEN::forkprocess(AST &p)
{ if (p) { p->emit2(); delete p; } }

// ++++++ code generation not requiring tree walk ++++++
void CGEN::newline(void)
{ emit(int(STKMC_nln)); }

void CGEN::writelnstring(CGEN_labels location)
{ emit(int(STKMC_prs)); emit(location); }

void CGEN::stackstring(char *str, CGEN_labels &location)
{ int l = strlen(str);
  if (stktop <= codetop + l + 1)
    { Report->error(212); generatingcode = false; return; }
  location = stktop - 1;
  for (int i = 0; i < l; i++) { stktop--; Machine->mem[stktop] = str[i]; }
  stktop--; Machine->mem[stktop] = 0;
}

void CGEN::dereference(AST &a)
{ /* not needed */ }

void CGEN::openstackframe(int size)
{ if (size > 0) { emit(int(STKMC_DSP)); emit(size); } }

void CGEN::leaveprogram(void)
{ emit(int(STKMC_HLT)); }

void CGEN::leavefunction(int blocklevel)
{ emit(int(STKMC_RET)); emit(blocklevel); emit(1); }

void CGEN::functioncheck(void)
{ emit(int(STKMC_NFN)); }

void CGEN::leaveprocedure(int blocklevel)
{ emit(int(STKMC_RET)); emit(blocklevel); emit(0); }

void CGEN::cobegin(CGEN_labels &location)
{ location = codetop; emit(int(STKMC_CBG)); emit(undefined); }

void CGEN::coend(CGEN_labels location, int number)
{ if (number >= STKMC_ProcMax) Report->error(216);
  else { Machine->mem[location+1] = number; emit(int(STKMC_CND)); } }

void CGEN::storelabel(CGEN_labels &location)
{ location = codetop; }

void CGEN::jump(CGEN_labels &here, CGEN_labels destination)
{ here = codetop; emit(int(STKMC_BRN)); emit(destination); }

void CGEN::backpatch(CGEN_labels location)
{ if (codetop == location + 2 &&
      STKMC_Opcodes(Machine->mem[location]) == STKMC_BRN)
  codetop -= 2;
  else
    Machine->mem[location+1] = codetop;
}

void CGEN::dump(void)
{ emit(int(STKMC_STK)); }

void CGEN::getsize(int &codeLength, int &initSP)
{ codeLength = codetop; initSP = stktop; }

int CGEN::getTop(void) { return codetop; }

----- clang.frm -----
/* Clang compiler generated by Coco/R 1.06 (C++ version) */
#include <stdio.h>

```

```

#include <fcntl.h>
#include <stdlib.h>
#include <string.h>

#if __MSDOS__ || MSDOS || WIN32 || __WIN32__
# include <iostream>
#else
# include <unistd.h>
# define O_BINARY 0
#endif

#include "misc.h"
#include "set.h"
#include "table.h"
#include "cgen.h"
#include "stkmc.h"

typedef Set<7> classset;

#include -->ScanHeader
#include -->ParserHeader
#include "cr_error.hpp"

static FILE *lst;
static char SourceName[256], ListName[256], CodeName[256];

TABLE *Table;
CGEN *CGen;
STKMC *Machine;
REPORT *Report;

class clangError : public CRError {
public:
    clangError(char *name, AbsScanner *S) : CRError(name, S, MAXERROR) {};
    virtual char *GetUserErrorMsg(int n);
    virtual char *GetErrorMsg(int n)
        { if (n <= MAXERROR) return ErrorMsg[n]; else return GetUserErrorMsg(n); }
private:
    static char *ErrorMsg[];
};

char *clangError::ErrorMsg[] = {
#include -->ErrorHeader
"User error number clash",
"";
};

char *clangError::GetUserErrorMsg(int n)
{ switch (n) {
    // first few are extra syntax errors
    case 91: return "Relational operator expected";
    case 92: return "Malformed expression";
    case 93: return "Bad declaration order";
    // remainder are constraint (static semantic) errors
    case 200: return "Constant out of range";
    case 201: return "Identifier redeclared";
    case 202: return "Undeclared identifier";
    case 203: return "Unexpected parameters";
    case 204: return "Unexpected subscript";
    case 205: return "Subscript required";
    case 206: return "Invalid class of identifier";
    case 207: return "Variable expected";
    case 208: return "Too many formal parameters";
    case 209: return "Wrong number of parameters";
    case 210: return "Invalid assignment";
    case 211: return "Cannot read this type of variable";
    case 212: return "Program too long";
    case 213: return "Too deeply nested";
    case 214: return "Invalid parameter";
    case 215: return "COBEGIN only allowed in main program";
    case 216: return "Too many concurrent processes";
    case 217: return "Only global procedure calls allowed here";
    case 218: return "Type mismatch";
    case 219: return "Unexpected expression";
    case 220: return "Missing expression";
    case 221: return "Boolean expression required";
    case 222: return "Invalid expression";
    case 223: return "Index out of range";
    case 224: return "Division by zero";
    default: return "Compiler error";
}
}

```

```

class clangReport : public REPORT {
// interface for code generators and other auxiliaries
public:
    clangReport(clangError *E)
    { Error = E; }
    virtual void error(int errorcode)
    { Error->ReportError(errorcode); errors = true; }
private:
    clangError *Error;
};

void main(int argc, char *argv[])
{ int codelength, initsp;
int S_src;
char reply;
lst = stderr;

// check on correct parameter usage
if (argc < 2) { fprintf(stderr, "No input file specified\n"); exit(1); }

// open the source file
strcpy(SourceName, argv[1]);
if ((S_src = open(SourceName, O_RDONLY | O_BINARY)) == -1)
{ fprintf(stderr, "Unable to open input file %s\n", SourceName); exit(1); }

if (argc > 2) strcpy(ListName, argv[2]);
else appendextension(SourceName, ".lst", ListName);
if ((lst = fopen(ListName, "w")) == NULL)
{ fprintf(stderr, "Unable to open list file %s\n", ListName); exit(1); }

// instantiate Scanner, Parser and Error handlers

-->ScanClass *Scanner = new -->ScanClass(S_src, -->IgnoreCase);
clangError *Error = new clangError(SourceName, Scanner);
-->ParserClass *Parser = new -->ParserClass(Scanner, Error);
Report = new clangReport(Error);
CGen = new CGEN(Report);
Table = new TABLE(Report);
Machine = new STKMC();

// parse the source
Parser->Parse();
close(S_src);

// generate source listing
Error->SetOutput(lst);
Error->PrintListing(Scanner);
fclose(lst);

// list generated code for interest
CGen->getsize(codelength, initsp);
appendextension(SourceName, ".cod", CodeName);
Machine->listcode(CodeName, codelength);

if (Error->Errors)
    fprintf(stderr, "Compilation failed - see %s\n", ListName);
else
{ fprintf(stderr, "Compilation successful\n");
while (true)
{ printf("\nInterpret? (y/n) ");
do
{ scanf("%c", &reply);
} while (toupper(reply) != 'N' && toupper(reply) != 'Y');
if (toupper(reply) == 'N') break;
scanf("%*[^\n]"); getchar();
Machine->interpret(codelength, initsp);
}
}

delete Scanner;
delete Parser;
delete Error;
delete Table;
delete Report;
delete CGen;
delete Machine;
}

```